

MOLY CHAIN LUBRICANT




LU™ 202



For use in extreme pressure applications



NSF® Registered; H2 Rated (Lubricants with no contact) (Registration # 115087)



Minimum - Maximum operational temperature range: Low -20 °F (-29 °C) • High 300 °F (149 °C)



Features Spray Anyway™ nozzle



HMS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Works under extreme pressure
- Penetrating foaming action
- Moly additive improves load ability



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™202 Moly Chain Lubricant is a high viscosity oil that clings to moving parts. Foaming action penetrates close tolerances of chain drive bushings and pins to provide long-lasting lubrication. Reduces friction wear on moving parts and in metal-to-metal applications. The 'moly' additive improves its capacity to handle greater pressure requirements of start-up stress. SPRAY ANYWAY™ Valve allows material to be applied to the surface when the can is being held in either upright or inverted position.

USES

- Chain drives and pins
- Forklift trucks
- Link and roller assemblies
- Machinery
- Work-stand rollers
- Assembly lines
- Packaging equipment
- Motorcycle and bicycle chains
- Sprockets
- Clippers
- Cutter bars
- Chain saws
- Bushings
- Hoist chains
- Conveyors
- Tractors



LU202

LUBRICANTS

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70 F.) Shake well before using. Spray at a distance of 10" to 12" from surface.

PERFORMANCE

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -20°F

HIGH: 300°F

LOAD CAPACITY: Extreme Pressure

- NSF Registration Number 115087; H2 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor
- Reduces friction wear on moving parts
- Lubricates between close tolerances
- Provides a penetrating 'foaming' action
- Lubricating film is long-lasting and non-drying
- Equipped with SPRAY ANYWAY™ valve and extension tube

PACKAGING

Stock #: S00202

UPC Code: 0-75577-90202-6

Fill Wt.: 11 oz.

Per Case: 12

Carton Dimensions:

L 10-7/8" x W 8-3/16" x H 8"

PROPERTIES

APPEARANCE: Light Amber

ODOR: Mild Solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 6.34

SPECIFIC GRAVITY: 0.76

PAINTABLE: No

% VOC AEROSOL: 31.80%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU202