


ANTI-SEIZE COMPOUND




LU™ 620



For use in extreme pressure applications



Blend of Nickel, Aluminum and Copper



Minimum - Maximum operational temperature range: Low -0°F (-18°C) High 2200°F (1204°C)



HMIS Hazard Rating:
Health (2) • Flammability (4) • Reactivity (0)

- Works From 0°F to +2200°F
- Meets MIL-PRF-907F
- Prevents seizure, galling, fusion
- Prevents corrosion, improves torque



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 620 Anti-Seize Compound is a combination of finely powdered metals that serve to protect against corrosion, seizure, galling, rust carbon fusion and galvanic pitting. This homogenized semi-synthetic lubricating grease will not melt and run out after application. Does not contain clay or soap base thickeners. Designed for preventative maintenance in marine, metal working, automotive, oil field, construction, mining, farm equipment and waste water and sewage. It also helps to reduce friction of metal surfaces.

USES

- Threaded fittings
- Plugs
- Sprockets and chains
- Rig drives
- Casting equipment
- Gaskets
- Winches
- Valve shafts
- Bushings
- Conveyors
- Splines and worm gears
- Manifold studs and bolts
- Brake cams and pins



LU620

LUBRICANTS

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 12" from surface.

PERFORMANCE

- PLASTIC SAFE: No
TEMPERATURE RANGE:
LOW: 0°F
HIGH: 2200°F
LOAD CAPACITY: Extreme Pressure
- Penetrant
 - Water-Displacer
 - Rust Inhibitor
 - Will not react with most gases
 - Equipped with an extension tube for hard-to-reach areas

PROPERTIES

- APPEARANCE: Copper gray
ODOR: Petroleum
PROPELLANT: Hydrocarbon
WT./GAL.: 6.03
SPECIFIC GRAVITY: 0.73
PAINTABLE: No
% VOC AEROSOL: 64%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: Yes
FLASH POINT: <0°F
HAZARD RATING: 2,4,0
SHELF LIFE: 3 years from date of manufacture

PACKAGING

- Stock #: S00620
UPC Code: 0-75577-90620-8
Fill Wt.: 11.25 oz.
Per Case: 12
Carton Dimensions:
L 11.13" x W 8.44" x H 8.38"

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:


1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU620